

电池产品规格书

BATTERIES SPECIFICATIONS

产品型号(MODEL NO.): BST-LR6 1.5V

制定(PREPARED): _____

审核(CHECKED): _____

批准(APPROVED): _____

客户审批 Customer Approved	审核 CHECKED	
	批准 APPROVED	
	请签名盖章确认后回传我司 Please sign and return one copy to us	盖章处 Seal the

BESTON reserve the right to alter or amend the design, model and specification without prior notice

修订履历

MODIFIED LIST

产品变更履历表

Product Modified Record List

Revision 版本	Date 日期	Mark 标记	Modified content 变更内容	Approved by 批准
V1.0	2014-4-21			

产品简介

Product Specification

品名：LR6 无汞碱性电池
电化学体系：锌-锰系列
标称电压：1.5V
电池总高：49.2~50.5mm
电池直径：13.5~14.5mm
包装：铝膜
保质期：3 年


Description: LR6 Mercury free Alkaline Battery
Chemical System: Zinc-Manganese Dioxide
Nominal Voltage: 1.5V
Nominal Height: 49.2~50.5mm
Nominal Dimension: 13.5~14.5mm
Jacket: Foil Label
Shelf Life: 3 Year

电性能特征 Electrical Characteristics


贮存环境 Storage Condition	初始期 Initial within 30day	贮存 12 个月 After 12months at 20±2℃
开路电压 Open-circuit voltage	1.550~1.650	1.500~1.650
10Ω continuous discharge End-point voltage: 0.9V	≥ 18.5h	≥ 17.5h
3.9Ω continuous discharge End-point voltage: 0.9V	≥ 360min	≥ 330min
43Ω 4hour/day discharge End-point voltage: 0.9V	≥ 80h	≥ 72h

LR6 “AA” SIZE 放电曲线

10 Ω Continuous Discharge Curve



3.9 Ω Continuous Discharge Curve



43 Ω 4hour/day Discharge Curve

